

# OUTLAW 4 RULES

Voted on 3/8/24

## 1. FRAMES:

- A) Stock frames - Unitized or tubular; no front wheel drive, rear wheel drive class only.

## 2. ENGINES:

- A) Stock blocks, cranks, heads, intake - porting is allowed.
- B) 11" engine setback centered in chassis; set measured between front of head and lower ball joints.
- C) Maximum 2500cc, no VTEC/variable valve engines or rotary engines.
- D) Naturally aspirated only. Headers allowed.
- E) Exhaust must exit behind driver.
- F) Exhaust must be shielded if routed through the car.

## 3. TRANSMISSION:

- A) Transmission stock with forward and reverse gears.

## 4. CARBURETOR:

- A) 500cfm carb max, 3" max spacers under carb.
- B) Choke housing removal allowed.
- C) No fuel injection.
- D) Any gasoline, no alcohol.

## 5. RADIATORS:

- A) In front of engine.

6. AXLES:

- A) Stock with at least 1/2-inch studs.
- B) No independent rear, no straight axles on front.

7. SPINDLES:

- A) Stock with at least 1/2-inch studs, stock brakes.

8. TIRES:

- A) 8 inch minimum, 10 inch maximum.
- B) Siping, grooving and grinding allowed.

9. WHEELS:

- A) 13, 14 or 15". 15" maximum, 8 inch wide - bead locks okay.

10. BODY:

- A) Fiberglass top okay, steel except front and rear plastics allowed, plastic skirt okay.
- B) Maximum 7-inch rear spoiler.

11. WEIGHT:

- A) 1 lb. per CC, weight recorded on both upper front fenders (driver included).

12. FUEL CELL:

- A) Mandatory, with foam inside and incased in steel.

13. ROLL CAGE:

- A) Must be a minimum 4-point cage with minimum 4 horizontal bars on driver side with two on passenger side, X behind driver.
- B) All cage components must be 1 3/4-inch OD X .090 pipe or 1 1/2-inch OD X .095 pipe. 14-

gauge metal (door plate) coverage on driver side, drive shaft area.

C) Battle bars within 2 inches of body on sides and radiused into the body.

14. DRIVE SHAFT:

A) Two hoops, metal or chain.

15. STEERING:

A) No center steer cars, left side steer only.

16. FIRE EXTINGUISHER:

A) Mandatory.

17. WHEEL BASE:

A) 94-inch wheel base minimum.